

## Functionality

- Device status light
- 3 disinfection cycle
  - Regular (8 minutes cycle)
  - Advanced (13 minutes cycle)
  - Rinsing and cleaning
- Fully automated
- Peristaltic pump 15 PSI
- Assembled on a sturdy base with 4 wheels of 8cm
- Entirely in stainless steel
- Easy operation and maintenance
- Child-safe design with power-off and emergency stop



since 2007

## Technical sheet

<b>Cycle capacity</b>	5 baskets or 6 small chairs
<b>Volume</b>	0,32 m3
<b>Water consumption per cycle</b>	7 liters
<b>Water temperature</b>	21 – 60o C / 70-140o F Temperature that maximizes disinfection is 54o C or 130 F
<b>Hot water supply</b>	½ OD, 2-5 Bars / 30-75 psi
<b>Evacuation and drainage</b>	¾ OD NPT Discharge rate : 20 gpm @ 35 psi
<b>Time cycle</b>	8 minutes
<b>External dimension</b>	161 cm height x 71 cm width x 66 cm deep 64 in height x 28 in width x 26 in deep
<b>Vibration</b>	Very weak
<b>Decibels</b>	65 dB
<b>Power supply</b>	Standard wall outlet 110 volts 15 amps
<b>Controle</b>	Programmable automaton
<b>Main pump</b>	1 HP
<b>Weight</b>	140 kg / 310 lbs
<b>Required clearance above unit</b>	10,16 cm / 4 in

**DESIGN, MANUFACTURING AND MAINTENANCE  
OF DESINFECTON APPARELS**