

### Functionality

- Bilingual device
- 3 disinfection cycle
  - Regular (8 minutes cycle)
  - Advanced (13 minutes cycle)
- Rinsing and cleaning
- CSA and UL certified, European conformity
- Fully automated
- Peristaltic pump 15 PSI
- Assembled on a sturdy base with 4 wheels of 8cm
- Entirely in stainless steel
- Easy operation and maintenance
- Touchscreen that displays the status of the device
- Reversible doors and handles
- External usb port for updates
- Child-safe design with power-off and emergency stop



### Technical sheet

|                                      |   |
|--------------------------------------|---|
| <b>Cycle capacity</b>                | 5 baskets or 6 small chairs   |
| <b>Volume</b>                        | 0,32 m3   |
| <b>Water consumption per cycle</b>   | 7 liters  |
| <b>Water temperature</b>             | 21 – 60o C / 70-140o F<br>Temperature that maximizes disinfection is 54o C or 130 F |
| <b>Hot water supply</b>              | ½ OD, 2-5 Bars / 30-75 psi  |
| <b>Evacuation and drainage</b>       | ¾ OD NPT<br>Discharge rate : 20 gpm @ 35 psi  |
| <b>Time cycle</b>                    | 8 minutes   |
| <b>External dimension</b>            | 161 cm height x 71 cm width x 66 cm deep<br>64 in height x 28 in width x 26 in deep |
| <b>Vibration</b>                     | Very weak   |
| <b>Decibels</b>                      | 65 dB   |
| <b>Power supply</b>                  | Standard wall outlet 110 volts 15 amps  |
| <b>Controle</b>                      | LCD touchscreen program   |
| <b>Main pump</b>                     | 1 HP  |
| <b>Weight</b>                        | 140 kg / 310 lbs  |
| <b>Required clearance above unit</b> | 10,16 cm / 4 in   |



**DESIGN, MANUFACTURING AND  
MAINTENANCE OF DESINFECTION APPARELS**

**UNIDEM**

632 A, ch. Sainte-Anne-Des-Lacs  
Sainte-Anne-Des-Lacs, QC J0R 1B0  
579 888-7888 • 1 888 970-0001

